

/ Data Sheet

Belt Conveyor - Model TDSL



Product Features and Structure:

- Modular design for a variety of series and models
- Heavy duty support structure for durability and safe operation
- Quiet operation and low energy consumption
- Carbon dioxide gas shielded welding workmanship
- CNC machining centres ensure precise fabrication
- Powder coated parts and components for best quality and duration

Technical Parameter

Model	Capacity		Belt Width	Line Speed	Conveying	Load Width	Length	Frame Width	Power	Lifting Power
	Bags/h	Bulk t/h	(mm)	(m/s)	Height (m)	(mm)	(m)	(mm)	(kW)	(kW)
TDSL50 x 6	720	45-60	500	1-3	1.8-2.2	- ≤600	6	686	2.2	0.75
TDSL50 x 8					2.0-3.7		8		2.2	
TDSL50 x 10					2.3-4.3		10		3.0	1.1
TDSL50 x 12					2.5-5.0		12		4.0	
TDSL50 x 15					2.8-6.5		15		4.0	1.5
TDSL50 x 18					3.4-7.3		18		5.5	
TDSL50 x 20					4.0-8.5		20		5.5	- 2.2
TDSL40 x 22					4.5-9.5		22		5.5	
TDSL65 x 6	720	60-80	650	1-3	2.0-2.5	- ≤750	6	836	2.2	0.75
TDSL65 x 8					2.0-3.7		8		3.0	
TDSL65 x 10					2.3-4.3		10		3.0	1.1
TDSL65 x 12					2.5-5.0		12		4.0	
TDSL65 x 15					2.8-6.5		15		4.0	1.5
TDSL65 x 18					3.4-7.3		18		5.5	
TDSL65 x 20					4.0-8.5		20		5.5	2.2
TDSL65 x 22					4.5-9.5		22		5.5	

Ashley Fraser

Seed & Grain Equipment World

PO Box 76, Rutherglen, Victoria 3685, Australia.

Phone +61 (0)418 176 764 Fax +61 (0)2 6032 9043

email: ash@sageworld.com.au

Call us today PH. 61 (0)418 176 764



www.sageworld.com.au