

/ Data Sheet

Corn Degerminator - Model TTPW



Product Features and Structure:

- A variety of series and models for a wide range of applications
- Rotor equipped with angled blades for assisting material flow in the working chamber
- Rotor dynamic balancing to ensure steady operation
- Special treatment applies to rotor blades for durability
- Flapper discharge complete with adjustment mechanism for optimal processing outcome
- Adjustable housing inserts to acquire demand impact strength
- Laser cutting applies to sheet metal components for quality and accuracy
- Carbon dioxide gas shielded welding workmanship
- CNC machining centres ensure precise fabrication
- Powder coated parts and components for best quality and duration

Technical Parameter

Model	Drum Diameter	Speed	Capacity	Power	Weight	Size L x W x H
	(mm)	(r/min)	(t/h)	(kW)	(kg)	(mm)
TTPW30 x 100	Ø 300	1320	3-4	22	710	2179 x 920 x 1710
TTPW30 x 150	Ø 300	1320	4-5	22	750	2365 x 920 x 1750
TTPW40 x 120 x 2	Ø 400	1320	9-10	22 x 2	1400	2000 x 1600 x 1782
TTPWA45 x 120	Ø 450	800	2-4	37	2800	223 x 894 x 1600
TTPWA65 x 120	Ø 650	800	4-7	45	3200	223 x 1094 x 1800
TTPWA75 x 125	Ø 750	800	7-10	55	3350	2273 x 1792 x 1870
						3068 x 1164 x 1870

Ashley Fraser

Seed & Grain Equipment World

PO Box 76, Rutherglen, Victoria 3685, Australia.

Phone +61 (0)418 176 764

Fax +61 (0)2 6032 9043

email: ash@sageworld.com.au

Call us today

PH. 61 (0)418 176 764



www.sageworld.com.au